

TECHNICAL PARAMETERS



DESCRIPTIONS

- The charger has ability to charge; (RVLA), Valve Regulated Batteries, Lead Acid Batteries and Deep Cycle Calcium Batteries.

Features	
• Microcontroller Integrated • 3-Stage Charging + Soft Start • Multi-rate Charging Options • Auto Switch-off & Recharge * • Intelligent Cooling Fan	• Multi Safety Protections: Polarity Reverse / Short Circuit / Overheat / Over Voltage / Over Current • Aluminum Housing

Model	MRW-EB-3620	MRW-EB-4820	MRW-EB-6020	MRW-EB-7220
Rating Voltage	36V	48V	60V	72V
Rating Capacity	20AH			
Charging Voltage	44.1±0.3V	59±0.2V	73.5±0.5V	88.2±0.5V
Charging current	2.6~3.0A			
Input Voltage	220V±20%AC,50/60HZ			
Lowest charging Voltage	23V±2V	35V±2V	40V±2V	47V±2V
Protection	-Short circuit protection			
	-Auto Power Off			
	-Thermal runaway protection			
	-Over heating protection			
	-Reverse connection protection			
Input line length	120cm			
Output line length	80cm			
Product Dimension (W*D*H)	170.5*90*55MM			
Net weight	537g			

