



ÖZELLİKLER (Features):

- KISA DEVRE/AŞIRI YÜK/YÜKSEK GERİLİM KORUMASI (SHORT CIRCUIT/OVERLOAD/OVER VOLTAGE PROTECTION)
- CE VE ROHS SERKİFİKASI (CE AND ROHS CERTIFICATION)
- KÜÇÜK VE ŞİK TASARIM (SMALL VE COMPACT SİZE)

TEKNİK BİLGİLER (SPECIFICATION):

MODEL		MS-1512 PL
ÇIKIŞ (OUTPUT)	DC ÇIKIŞ (DC VOLTAGE)	12V
	ÇIKIŞ AKIMI (RATED CURRENT)	1.0 A
	ÇIKIŞ GÜCÜ (RATED POWER)	15W
GİRİŞ (INPUT)	VOLTAJ ARALIĞI (VOLTAGE RANGE)	100-240VAC
	FREKANS ARALIĞI (FRE. RANGE)	47-63HZ
	VERİMLİLİK (EFFICIENCY)	77.86%full load
KORUMA (PROTECTION)	AŞIRI YÜK (OVER LOAD)	KAPANMA, YENİDEN BESLEME İLE ÇALIŞMA (SHUT OFF, AC RECYCLE TO RE-START)
ÇALIŞMA ORTAMI (ENVIRONMENT)	ÇALIŞMA SICAKLIĞI VE NEM (WORKING TEMP. & HUMIDITY)	0~+40°C / 20-90% RH
	DEPOLAMA SICAKLIĞI VE NEM (STORAGE TEMP. & HUMIDITY)	-20~+70°C / 10-95% RH
BOYUTLAR (DIMENSION)		135*25*17mm (L*W*H)

MEKANİK ÖZELLİKLER (MECHANICAL SPECIFICATION)

