



ÖZELLİKLER (Features):

- KISA DEVRE, AŞIRI YÜK KORUMASI
(SHORT CIRCUIT, OVER LOAD PROTECTION)
- CE SERKİFİKASI (CE CERTIFICATION)
- KÜÇÜK VE ŞİK TASARIM (SMALL VE COMPACT SIZE)

TEKNİK BİLGİLER (SPECIFICATION):

MODEL		MS-6024
ÇIKIŞ (OUTPUT)	DC ÇIKIŞ (DC VOLTAGE)	24 V (Costant Voltage)
	ÇIKIŞ AKIMI (OUTPUT CURRENT)	2.5 Amper
	ÇIKIŞ GÜCÜ (RATED POWER)	60 W
GİRİŞ (INPUT)	VOLTAJ ARALIĞI (VOLTAGE RANGE)	100-240VAC
	FREKANS ARALIĞI (FRE. RANGE)	47~63Hz
	VERİMLİLİK (EFFICIENCY)	87.0% full load
KORUMA (PROTECTION)	AŞIRI YÜK (OVER LOAD)	KAPANMA, YENİDEN BESLEME İLE ÇALIŞMA (SHUTT OFF, AC RECYCLE TO RE-START)
ÇALIŞMA ORTAMI (ENVIRONMENT)	ÇALIŞMA SICAKLIĞI VE NEM (WORKING TEMP. & HUMIDITY)	0~+40°C / 20-90% RH
	DEPOLAMA SICAKLIĞI VE NEM (STORAGE TEMP. & HUMIDITY)	-20~+70°C / 10-95% RH
BOYUTLAR (DIMENSION)		120*52.5*32mm (L*W*H)

MEKANİK ÖZELLİKLER (MECHENICAL SPECIFICATION)

