



### ÖZELLİKLER (Features):

- KISA DEVRE/AŞIRI YÜK KORUMASI  
(SHORT CIRCUIT/OVERLOAD PROTECTION)
- 100 % TAM YÜKTE ÇALIŞMA  
(100 % FULL LOAD WORKING)
- CE SERKİFİKASI (CE CERTIFICATION)
- KÜÇÜK VE ŞİK TASARIM (SMALL VE COMPACT SIZE)

### TEKNİK BİLGİLER (SPECIFICATION):

MODEL		MT-150-5	MT-150-12	MT-150-24	MT-150-48
ÇIKIŞ (OUTPUT)	DC ÇIKIŞ (DC VOLTAGE)	5 V	12 V	24 V	48 V
	ÇIKIŞ AKIMI (RATED CURRENT)	30 A	12.5 A	6.5A	3.2A
	AKIM ARALIĞI (CURRENT RANGE)	0-30 A	0-12.5 A	0-6.5A	0-3.2A
	ÇIKIŞ GÜCÜ (RATED POWER)	150 W	150 W	156 W	153.6 W
	DALGALANMA & GÜRÜLTÜ (RIPPLE & NOISE)	100m Vp-p	120m Vp-p	200m Vp-p	240m Vp-p
	VOLTAJ AYAR ARALIĞI (VOLTAGE ADJ. RANGE)	4.5-5.5 V	10.8-13.2 V	21.6-26.4 V	44-52 V
	VOLTAJ TOLERANSI (V.TOL.)	±2.0%	±1.0%	±1.0%	±1.0%
	YÜK (LOAD) REGÜLASYONU	±1.0%	±1.0%	±1.0%	±1.0%
	KALKIŞ ZAMANI (SETUP, TIME)	2000ms, 230VAC TAM YÜKTE (AT FULL LOAD)			
GİRİŞ (INPUT)	VOLTAJ ARALIĞI (VOLTAGE RANGE)	176-264VAC			
	FREKANS ARALIĞI (FRE. RANGE)	47~63Hz			
	VERİMLİLİK (EFFICIENCY)	78% full load	82% full load	84% full load	86% full load
	KALKIŞ DAYANIM AKIMI (INRUSH CURRENT)	Cold Start, 40A/230VAC			
	SIZINTI AKIMI (LEAKAGE CURRENT)	3.5mA(max)/240VAC			
KORUMA (PROTECTION)	AŞIRI YÜK (OVER LOAD)	110% - 150% ÇIKIŞ GÜÇ ARALIĞINDA (rated output power)			
		KAPANMA, YENİDEN BESLEME İLE ÇALIŞMA (Hiccup mode, auto-recovery)			
ÇALIŞMA ORTAMI (ENVIRONMENT)	ÇALIŞMA SICAKLIĞI VE NEM (WORKING TEMP. & HUMIDITY)	-10~+40°C / 20~90 % RH			
	DEPOLAMA SICAKLIĞI VE NEM (STORAGE TEMP. & HUMIDITY)	-20~+85°C / 20~95 % RH			
BOYUTLAR (DIMENSION)/WEIGHT		199*98*42mm (L*W*H)/0.68KGS			