



### ÖZELLİKLER (Features):

- KISA DEVRE/AŞIRI YÜK KORUMASI  
(SHORT CIRCUIT/OVER LOAD PROTECTION)
- 100 % TAM YÜKTE ÇALIŞMA  
(100 % FULL LOAD WORKING)
- CE SERKİFİKASI (CE CERTIFICATION)
- KÜÇÜK VE ŞİK TASARIM (SMALL VE COMPACT SIZE)

### TEKNİK BİLGİLER (SPECIFICATION):

MODEL		MT-200-5	MT-200-12	MT-200-24	MT-200-48
ÇIKIŞ (OUTPUT)	DC ÇIKIŞ (DC VOLTAGE)	5V	12V	24V	48V
	ÇIKIŞ AKIMI (RATED CURRENT)	40A	16.5A	8.3A	4.2A
	AKIM ARALIĞI (CURRENT RANGE)	0-40A	0-16.5A	0-8.3A	0-4.2A
	ÇIKIŞ GÜCÜ (RATED POWER)	200W	198W	199.2W	201.6W
	DALGANLAMA & GÜRÜLTÜ (RIPPLE & NOISE)	100m Vp-p	100m Vp-p	150m Vp-p	150m Vp-p
	VOLTAJ AYAR ARALIĞI (VOLTAGE ADJ. RANGE)	4.5-5.5V	10.8-13.2 V	21.6-26.4 V	43.2-52.8 V
	VOLTAJ TOLERANSI (V.TOL.)	±2%	±2%	±2%	±2%
	YÜK (LOAD) REGÜLASYONU	± 1%	± 1%	±1%	±1%
	KALKIŞ ZAMANI (SETUP, TIME)	50ms, 230VAC TAM YÜKTE (AT FULL LOAD)			
GİRİŞ (INPUT)	VOLTAJ ARALIĞI (VOLTAGE RANGE)	176~264VAC			
	FREKANS ARALIĞI (FRE. RANGE)	47~63Hz			
	VERİMLİLİK (EFFICIENCY)	78% full load	80% full load	83% full load	84% full load
	KALKIŞ DAYANIM AKIMI (INRUSH CURRENT)	30A/230VAC			
	SIZINTI AKIMI (LEAKAGE CURRENT)	3.5mA(max)/240VAC			
KORUMA (PROTECTION)	AŞIRI YÜK (OVER LOAD)	110% - 150% ÇIKIŞ GÜÇ ARALIĞINDA (rated output power)			
		KAPANMA, YENİDEN BESLEME İLEÇALIŞMA (SHUTT OFF, AC RECYCLE TO RE-START)			
ÇALIŞMA ORTAMI (ENVIRONMENT)	ÇALIŞMA SICAKLIĞI VE NEM (WORKING TEMP. & HUMIDITY)	-10~+40°C / 20~90 % RH			
	DEPOLAMA SICAKLIĞI VE NEM (STORAGE TEMP. & HUMIDITY)	-20~+85°C / 20~95 % RH			
BOYUTLAR (DIMENSION)/WEIGHT		199*110*50mm (L*W*H)/0.8KGS			