



ÖZELLİKLER (Features):

- AC GİRİŞ (220)
- KISA DEVRE/AŞIRI YÜK/YÜKSEK GERİLİM KORUMASI
(SHORT CIRCUIT/OVER LOAD/OVER VOLTAGE PROTECTION)
- 100 % TAM YÜKTE ÇALIŞMA
(100 % FULL LOAD WORKING)
- 2 YIL GARANTİ (2 YEARS WARRANTY)
- CE SERKİFİKASI (CE CERTIFICATION)
- KÜÇÜK VE ŞİK TASARIM (SMALL VE COMPACT SIZE)

EKNİK BİLGİLER (SPECIFICATION):

MODEL		MS-800-12	MS-750-24	MS-800-48
ÇIKIŞ (OUTPUT)	DC ÇIKIŞ (DC VOLTAGE)	12 V	24V	48V
	ÇIKIŞ AKIMI (RATED CURRENT)	66A	31A	16.6A
	AKIM ARALIĞI (CURRENT RANGE)	0-66A	0-31A	0-16.6A
	ÇIKIŞ GÜCÜ (RATED POWER)	792 W	744W	796.8W
	DALGANMA & GÜRÜLTÜ (RIPPLE & NOISE)	150m Vp-p	200m Vp-p	300m Vp-p
	VOLTAJ AYAR ARALIĞI (VOLTAGE ADJ. RANGE)	10.8-13.2 V	21.6-26.4V	44-52V
	VOLTAJ TOLERANSI (V.TOL.)	±1%	±1%	±0.5%
	YÜK (LOAD) REGÜLASYONU	±0.5%	±0.5%	±0.5%
	KALKIŞ ZAMANI (SETUP, TIME)	800ms, 230VAC TAM YÜKTE (AT FULL LOAD)		
GİRİŞ (INPUT)	VOLTAJ ARALIĞI (VOLTAGE RANGE)	180-260 VAC		
	FREKANS ARALIĞ (FRE. RANGE)	47~63Hz		
	VERİMLİLİK (EFFICIENCY)	80% full load	85% full load	86% full load
	KALKIŞ DAYANIM AKIMI (INRUSH CURRENT)	75A/230VAC		
	SIZINTI AKIMI (LEAKAGE CURRENT)	3.5mA/240VAC		
KORUMA (PROTECTION)	AŞIRI YÜK (OVER LOAD)	110% - 150% ÇIKIŞ GÜÇ ARALIĞINDA (rated output power) KAPANMA, YENİDEN BESLEME İLE ÇALIŞMA (SHUTT OFF, AC RECYCLE TO RE-START)		
	AŞIRI VOLTAJ (OVER VOLTAGE)	14-18 V	28-36V	55-72V
		KAPANMA, YENİDEN BESLEME İLE ÇALIŞMA (SHUTT OFF, AC RECYCLE TO RE-START)		
ÇALIŞMA ORTAMI (ENVIRONMENT)	ÇALIŞMA SICAKLIĞI VE NEM (WORKING TEMP. & HUMIDITY)	-10~+40°C / 20~90 % RH		
	DEPOLAMA SICAKLIĞI VE NEM (STORAGE TEMP. & HUMIDITY)	-20~+85°C / 20~90 % RH		
GÜVENLİK & STANDARTLAR (SAFETY)	GÜVENLİK STANDARTLARI (SAFETY STANDARDS)	Refer to GB4943 UL60950-1		
	MTBF	50.000 HOURS MİN 25°C		
BOYUTLAR (DIMENSION)/WEIGHT		291*133*68mm (L*W*H)/2.6KGS		